PRO-FORCE

Reinforcement Matting for Liquid Systems

Reference Date:
Issue 3,
June 2021

DATASHEET

PRO-FORCE (GLASS FIBRE) IS TO BE USED TO REINFORCE LIQUID WATERPROOFING MATERIALS WHEN STRUCTURAL MOVEMENT IS ANTICIPATED OR WHEN THE GENERAL REINFORCING OF THE WATERPROOFING MATERIAL IS REQUIRED

1. Applications

- All areas subject to structural or thermal movement
- Changes to substrate
- Pipes and protrusions

2. Benefits

- Good mechanical properties
- Long shelf life
- Available in various sizes, cutting down wastage
- Light- weight, flexible and easy to apply
- Easy to cut and shape

3. Durability

- Pro-Force reinforcing fabrics must be laid into the first coat of waterproofing which must be allowed to dry prior to the application of the second coat
- A full or partial layer of Pro-Force depend on the system specification

4. Typical Physical & Performance Data

Form	E-Glass matting bound with an emulsion binder
Colour	Off White
Fabric Weight	225g/Mtr²
Roll Size	150mm x 20m : 1m x 20m : 1.05m x 119m (125m²)

All products should be sold in accordance with the manufacturer's instructions. No responsibility can be taken by the manufacturers where conditions of use are beyond our control. Proteus Waterproofing products are available for sale in accordance with our standard terms and conditions of sale which are available on request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us or our representatives, agents, or distributors, as the conditions of use and any labour involved are beyond our control. Our warranty is therefore limited to the quality of the supplied product

Proteus Waterproofing Limited
21a Sirdar Road
Brook Road Industrial Estate
Rayleigh
Essex SS6 7XF

Tel: 01268 777 871
Email: office@proteuswaterproofing.co.uk
www.proteuswaterproofing.co.uk

Registered Office: Charter House, 105 Leigh Road, Leigh-On-Sea, Essex, SS9 1JL I Registered company number: 08458402